

DH-PFM325D-1210EN

DC12V 1A Power Adapter



- · Supports desktop mount, making it highly convenient to use.
- · Shell flame resistance V-0 level.
- · Protects against overcurrent, overvoltage, and short circuits.
- Efficiency Level: VI.

Series Overview

Dahua Power Adapter meets both national and regional certificate requirements. It offers outstanding performance and stable output, is environmentally friendly, and makes reliable use of electricity. The adapter comes with overvoltage protection, overload protection and more. It is also plug-and-play, making it easy and convenient to use.

Technical Specification		
Function		
Input Voltage	100-240 VAC	
Output Voltage	12 V ± 5%	
Rated Output Current	1 A	
Rated Power	12 W	
Power Consumption In Idle	≤0.1 W	
Efficiency	≥82.96%	
Indicator Light	Green light x 1	
Port		
Input Port	European Standard 2 pin plug	
Output Plug	Φ 5.5 mm × Φ 2.1 mm × 10.0 mm (0.22" × 0.08" × 0.39") (OD × ID × L)	
Protection		
Types of Protection	Protects against overcurrent, overvoltage, short circuits.	
Surge Protection Grade	Common mode: ±2 kV Differentiate mode: ±1 kV	
Statics Protection	Air discharge: ±8 kV Contact discharge: ±6 kV	

Structure

Installation	Desktop mount	
Product Dimensions	95.0 mm x 34.8 mm x 28.0 mm (3.74" x 1.37" x 1.10")	
Appearance Color	Black	
Net Weight	0.1 kg (0.22 lb)	
Gross Weight	0.115 kg (0. 5 lb)	
Packaging Dimensions	72.0 mm x 44.0 mm x 122.0 mm (2.83" x 1.73" x 4.80")	
Input Cable Length	350 mm (13.78")	
Output Cable Length	800 mm (31.50")	
Environment		
Operating Temperature	Full load: -20 °C to +40 °C (-4 °F to +104 °F) 80% load: +40 °C to +55 °C (+104 °F to +131 °F)	
Operating Humidity	10%-90% (RH)	
Storage Temperature	-10 °C to +70 °C (+14 °F to + 158 °F)	
Storage Humidity	10%-90% (RH)	
Certifications		
Certifications	CE	

Ordering Information			
Туре	Model	Description	
Power Adapter	DH-PFM325D-1210EN	DC12V 1A Power Adapter	

Dimensions (mm[inch])

