

M20-PoE

5 Port Cloud Managed PoE Router



M20-PoE

5 Port Cloud Managed PoE Router

Products Description

M20-PoE integrates router, PoE switch, and access controller altogether. Dedicated 4× PoE+ Ports for PoE-supported devices such as access points, IP cameras, and IP phones, lowering infrastructure costs for small businesses.

M20-PoE supports pass-through traffic and multiple VPN protocols, including IPSec, PPTP, and L2TP. Intelligent load balancing and link redundancy between multiple WAN ports.

Key Feature

- Integrates router, PoE switch, and controller altogether.
- Dual-Core CPU provides 1Gbps forwarding performance
- Up to 4× WAN Ethernet Ports , Support load balancing
- 4× 802.3at/af-compliant PoE+ ports yield a total power supply of 55W*.
- Supports IPsec VPN, and L2TP/PPTP VPN connections.

Product Features



Cloud Managed

Supports ProFi Cloud , Remote monitoring and maintenance.



Efficient firewall to ensure internal and external network security

Support attack defense function, effectively resisting various common DoS attacks, DDoS attacks, ARP attacks, flooding attacks and scanning attacks.

Support IP and MAC address binding, effectively preventing ARP spoofing.

Support MAC address-based filtering to block unauthorized hosts from accessing.

Support URL filtering to prevent users from accessing risky domain names, and reduce network risks.



55W PoE Budget

Support 4× PoE+ Ports for PoE-supported devices such as access points, IP cameras, and IP phones.



Multiple WAN ports with multiple broadband access


supports up to 4 WAN ports. It can realize bandwidth stacking with 4 broadband lines, and the stacking efficiency can reach 98%. In addition, it supports intelligent routing, automatic traffic balancing and custom traffic balancing to fully utilize bandwidth resources.



Easy Installation

compact design for desktop and wall mounting, makes it suitable for various spaces.

Application Scenario



Related Products



Pro-6-iw

- 2.4 GHz Band up to 574 Mbps
- 5 GHz Band up to 2402 Mbps
- Fast roaming at 50 ms
- Double-sided tape installation



Pro-6-lite

- 2.4 GHz Band up to 574 Mbps
- 5 GHz Band up to 2402 Mbps
- Small and compact
- Fast roaming at 50 ms

Product Specifications

Product Informations	
Basic Information	M20-PoE
Installation	Desktop
Dimensions (L*W*H)	100*100*26mm
Application Scenario	Enterprise Office
Operation mode	Router Mode
Performance Parameters	
Max. Client Capacity	150
Recommended Client Capacity	100
Recommended broadband	1000Mbps
Max. New Sessions	4000
Max. Concurrent Sessions	42000
NAT (Static IP)	940Mbps/930Mbps
NAT(DHCP)	941Mbps/932Mbps
NAT(PPPoE)	914Mbps/924Mbps
AP Management	16
VLAN	4
Hardware Parameters	
CPU	Dual Core, 1.0GHz
RAM	128MB
FLASH	16MB
Ports	5*GE (Max. 4 WAN, Max. 4 LAN)
PoE output	802.3af/at on LAN1-4
PoE Budget	55W
Button	Reset Button
Standards and Protocols	IEEE 802.3, 802.3u, 802.3x, TCP/IP, DHCP, ICMP, NAT, PPPoE, NTP, HTTP, DDNS
Power Supply	51VDC/1.25A Adapter
Software Parameters	
AP Management	16
DHCP Server	DHCP Server(User/AP),DHCP Reservation
Wireless Policy	AP Group,SSID Policy,RF Policy,Vlan Policy,maintenance policy,Alarm Policy,Deployment Policy
Fast roaming	802.11k,v,r
IPTV	IPTV Policy

Product Specifications

ACL	IP/MAC/URL/PORT
Bandwidth Control	Based on single user, user group, smart bandwidth control
VPN	IPSec, PPTP, L2TP
Virtual Server	DMZ, DDNS, DNS Hijacking, IP Hijacking, UPNP, Port Mirroring, Port Mapping, DNS Cache
IPV6	Support
WAN Load Balancing	Intelligent Load Balancing, Customize
Routing	Static Routing, Policy Routing
Security	IP-MAC binding, Block Ping from WAN, DDoS Attack Defense, ARP Attack Defense, Binary Association
System Tools	ntp, Scheduled reboot, Diagnosis
system log	system log, Operating log, Running log
System Account	Administrator, Visitor, Login IP Address Limit
Upgrade	Local, Online
Maintenance	Restore, Backup, Remote WEB Management
Management	http/https, ProFi Cloud, ProFi APP
Other Parameters	
Environment	Operating Temperature: -10°C-45°C Operating Humidity: 10%-90% RH, non-condensing Storage Temperature: -40-70°C Storage Humidity: 5%-90% RH, non-condensing



IP-COM NETWORKS CO.,LTD.

Tower E3, No.1001, Zhongshanyuan Road,
Nanshan District, Shenzhen, China. 518052
Service: info@ip-com.com.cn
Inquiry: marketing@ip-com.com.cn
Tel: +86-755-27653089